



 **GLOSS**

2024



Content

	Spray guns	2
	Accessories for spray guns	6
	Air filtration	9
	Mixing cups	12
	Tools and equipment	13
	Masking foils	20
	Insulating materials	22
	Cleaning products	23

GLOSS GH-SH

Low Volume and Medium Pressure spray gun creates smooth atomization of all kind of metallic paint and clearcoat. Modern body design creates comfortable handling.

- L.V.M.P
- Purpose: Basecoat and Clearcoat
- Working pressure: 2,5 bar
- Pattern width: 280 mm
- Air consumption: 254-311 l/min
- Spray distance: 200 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 600 ml
- Nozzle 1,3 mm - for paints, clearcoats
- Nozzle 1,4 mm - for primers

Code	Nozzle	Packaging
GH-SH 1.3	1,3 mm	1 pc
GH-SH 1.4	1,4 mm	1 pc

GLOSS GH-SH (MINI)

High Volume and Low Pressure spray gun is designed for quick repair processes. Excellent spraying efficiency. High quality stainless steel nozzle and needle. Suitable for waterborne paints as well. Ideal for part painting.

- H.V.M.P
- Purpose: Basecoat and Clearcoat
- Working pressure: 1,5 bar
- Pattern width: 120 mm
- Air consumption: 142-198 l/min
- Spray distance: 150 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 250 ml
- Nozzle 1,0 mm - for paints, clearcoats

Code	Nozzle	Packaging
GH-SH mini	1,0 mm	1 pc





GLOSS GMP-500

High Volume and Low Pressure spray gun is suitable for applying acrylic products, spray putty and basecoat paint. The spray gun body is covered with chrome-effect paint.

- H.V.L.P.
- Purpose: Primer/Filler, Acrylic paint and Clearcoat
- Working pressure: 2,0 bar
- Pattern width: 280 mm
- Air consumption: 283 - 311 l/min
- Spray distance: 170 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 600 ml
- Nozzle 1,3 mm - for paints, clearcoats
- Nozzle 1,8 mm - for fillers

Code	Nozzle	Packaging
GMP-500	1,3 mm	1 pc
GMP-500 1.8	1,8 mm	1 pc



GLOSS GMP-102 (MINI)

High Volume and Low Pressure mini spray gun is perfect tool to spray small areas with acrylic products and basecoat paints.

- H.V.L.P.
- Purpose: Spot repair and Aerography
- Working pressure: 2,0 bar
- Pattern width: 100 mm
- Air consumption: 141 - 155 l/min
- Spray distance: 150 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 250 ml
- Nozzle 1,0 mm - for paints, clearcoats

Code	Nozzle	Packaging
GMP-102	1,0 mm	1 pc



GLOSS GH-827RPX

High Volume and Low Pressure spray gun will atomize acrylic fillers easily and smoothly. The spray gun body comes with chrome-effect paint, making cleaning easier.

- H.V.L.P.
- Purpose: Primer/Filler
- Working pressure: 3,0 - 3,5 bar
- Pattern width: 240 mm
- Air consumption: 254 - 311 l/min
- Spray distance: 200 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 600 ml
- Nozzle 1,4 mm - for primers
- Nozzle 1,8 mm - for fillers
- Nozzle 2,0 mm - for fillers
- Nozzle 2,5 mm - for spray putty

Code	Nozzle	Packaging
GH-827RPX	1,4 mm	1 pc
GH-827RPX1.8	1,8 mm	1 pc
GH-827RPX2.0	2,0 mm	1 pc
GH-827RPX2.5	2,5 mm	1 pc



GLOSS GH-827X

Low Volume and Medium Pressure spray gun creates a smooth atomization of all kinds of metallic paint and clearcoat.

- L.V.M.P.
- Purpose: Basecoat and Clearcoat
- Working pressure: 2,0 - 2,5 bar
- Pattern width: 260 mm
- Air consumption: 311 - 368 l/min
- Spray distance: 200 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 600 ml
- Nozzle 1,3 mm - for paints, clearcoats

Code	Nozzle	Packaging
GH-827X	1,3 mm	1 pc

GLOSS GH-GLG

Low Volume and Medium Pressure atomization spray gun applies acrylic paint and clearcoat perfectly. It is very easy to maintain due to its smooth body.

- L.V.M.P.
- Purpose: Primer/Filler, Acrylic paint and Clearcoat
- Working pressure: 2,5 bar
- Pattern width: 280 mm
- Air consumption: 255-311 l/min
- Spray distance: 200 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 600 ml
- Nozzle 1,3 mm - for paints, clearcoats
- Nozzle 1,4 mm - for clearcoats, primers
- Nozzle 1,8 mm - for fillers

Code	Nozzle	Packaging
GH-GLG 1.3	1,3 mm	1 pc
GH-GLG 1.4	1,4 mm	1 pc
GH-GLG 1.8	1,8 mm	1 pc



GLOSS GH-2000X

High Volume and Low Pressure mini spray gun provides optimum atomisation, in overspray while effectively covering small areas with acrylic products and basecoat paints.

- H.V.L.P.
- Purpose: Spot repair and Aerography
- Working pressure: 2,0 bar
- Pattern width: 100 mm
- Air consumption: 141 - 155 l/min
- Spray distance: 150 mm
- Air Inlet: 1/4" Universal Thread
- Cup capacity: 125 ml
- Nozzle 0,8 mm - for paints, clearcoats

Code	Nozzle	Packaging
GH-2000X	0,8 mm	1 pc



ACCESSORIES FOR SPRAY GUNS



GLOSS SPRAY GUN GRAVITY CUP

Painting cup for spray gun with a M16x1.5 / M16x2 thread.

GLOSS PAINT FILTERS

Universal gravity feed spray gun paint filter effectively removes various dirt residues. It is resistant to most solvents and easy to clean.



Code	Description	Capacity	Packaging
GPC600A	male thread	600 ml	1 pc
GPC-600GPP	femal thread	600 ml	1 pc



Code	Description	Packaging
GF-10	10 pcs	1 set

ACCESSORIES FOR SPRAY GUNS



GLOSS PRESURE REGULATOR

Air pressure gauge with regulator and manometer accurately controls paint atomization during spraying. It is suitable for every spray gun.

- Air consumption: 362 l/min at 3 bar
- Air Inlet: 1/4" BSP
- Waterproof, solvent resistant



Code	Packaging
GFR-5	1 pc

GLOSS FLEXIBLE JOINT

Flexible metal sprayer connection is designed to allow free movement during painting.



Code	Description	Packaging
OP20MS1	1/4 male	1 pc
OP20FS1	1/4 female	1 pc

GLOSS AIR COUPLERS

Pneumatic coupling is used to connect compressed air tools to a compressed air line. It allows a tool to be easily connected or disconnected to a hose or pipe while it is under pressure.



Code	Dimensions	Packaging
G-EPF20 (Female)	1/4"	1 pc
G-EPM20 (Male)	1/4"	1 pc
G-ESH20-8	8 mm	1 pc
G-ESH20-10	10 mm	1 pc

GLOSS PVC AIR HOSE

High-pressure air hose with a quick coupling and nipple.



Code	Dimensions	Packaging
G-HOSE15	8*12 mm x 15 m	1 pc

GLOSS PROFESSIONAL AIR FILTER AC-6002

Air filter with pressure regulator and outlet module. Filtering particles less than 0,01 microns. Providing clean compressed air - with a separation degree of 99,998%.



- Air flow: 2300 l/min at 10 bar
- Max. operating temperature 60 °C
- Air inlet: 1/2"
- Two outlet valves 1/4"

Code	Packaging
AC-6002	1 pc

GLOSS PROFESSIONAL AIR FILTER AC-6003

Triple-stage filter unit complete with a fine filter and activated charcoal cartridge with an air outlet module, filtering particles less than 0.01 microns. Providing clean compressed air with a separation degree of 99.998%.



- Air flow: 2000 l/min at 10 bar
- Max. operating temperature 60 °C
- Air inlet: 1/2" internal thread
- Two outlet valves 1/4" bsp external thread

Code	Packaging
AC-6003	1 pc



10



GLOSS CARTRIDGE FOR FILTER AC-6002/AC-6003

Replaceable fine filter cartridge: separates particles greater than 0.01 microns. It must be replaced when the pressure difference indicated by these two gauges is more than 0.8 bar.

Code	Packaging
AC6000-366	1 pc



GLOSS CARTRIDGE FOR FILTER AC-6003

Activated charcoal filter: removes particles less than 0.01 microns, oil vapour and organic odours. It should be replaced every 3 months.

Code	Packaging
AC6000-369	1 pc



GLOSS OIL AND WATER SEPARATOR

Eliminates water, oil, dust, and particles in air line from air compressor. Can be directly connected to paint airbrush, air compressors and other pneumatic tools.

11

- Inlet and outlet: universal 1/4" NPT
- Operating temp.: -5 °C to 55 °C
- Max. Pressure: 6 bar

Code	Packaging
GF04	1 pc

MIXING CUPS



12



GLOSS MIXING CUPS

Graduated plastic mixing cups and lids. Mixing cups are solvent resistant. Printed markings on outside of cup make mixing easy and accurate.

Code	Capacity	Packaging
GMC 0385	cup 385 ml	200 pcs
GMC 0750	cup 750 ml	200 pcs
GMC 1400	cup 1400 ml	200 pcs
GMC 2300	cup 2300 ml	100 pcs
GCL 0385	lid 385 ml	200 pcs
GCL 0750	lid 750 ml	200 pcs
GCL 1400	lid 1400 ml	200 pcs
GCL 2300	lid 2300 ml	100 pcs

GLOSS CENTRAL VACUUM RANDOM ORBITAL SANDER

Orbital air sander is perfect for bodywork sanding. The air sander features a compact palm grip that lets you reach tight spots easily, a paddle trigger and a built-in regulator.



- Pad size: 150 mm
- Orbit: 5 mm
- Free speed: 11000 rpm
- Air consumption: 354 l/min at 6,2 bar
- Net weight: 0,9 kg

Code	Packaging
GST-7138DC-6	1 pc

GLOSS PNEUMATIC ORBITAL SANDER

Orbital air sander is perfect for bodywork sanding! The air sander features a compact palm grip that lets you reach tight spots easily, a paddle trigger and a built-in regulator.



- Pad size: 150 mm
- Orbit: 5 mm
- Free speed: 10500 rpm
- Air consumption: 354 l/min at 6,2 bar
- Net weight: 0,98 kg

Code	Packaging
GSM00	1 pc



GLOSS PROFESIONAL SAND BLASTER KIT

Air Sandblaster Kit is a very handy for removing rust, lime scale, chemicals and paint it will also bring out the shine in almost all dull metals and is ideal for restoration work. Sandblasting is the ideal way to clean metal rims on car wheels, remove rust from fences, refurbish external brickwork.

Code

SA-6602

Packaging

1 pc



GLOSS MINI AIR ANGLE SANDER

Ideal for metal grinding, deburring and multi-purpose refinishing in any industrial application.



- Capacity: 6 mm
- Free speed: 20000 rpm
- Air consumption: 85 l/min
- Net weight: 0,49 kg

Code	Packaging
GST-P7734M	1 pc



GLOSS 2" AIR ANGLE SANDER

Ideal for metal grinding, deburring and multi-purpose refinishing in any industrial application.

15



- Pad size: 50.8 mm
- Free speed: 18000 rpm
- Air consumption: 283 l/min
- Net weight: 0,8 kg

Code	Packaging
GST-AS10N2R	1 pc

GLOSS / Oil-free
Technology

Fast Storage , High Flow Supply



High flow
rate



Oil-free



Low noise



Low
vibration



8bar high
pressure



High speed
silenced
motor



Overload
protection



Low
temperature
rise

Fast Storage , High Flow Supply





GLOSS OIL FREE AIR COMPRESSOR, AIR TANK 24L

High quality single engine oil-free air compressor.
High air efficiency. Low vibration. Low noise level.
Overheat protection.

17

- Air efficiency: at 8 bar - 100 l / min
- Air efficiency: at 4 bar - 145 l / min
- Capacity: 24 l
- Weight: 21 kg

Code	Packaging
2-1450F24	1 pc



GLOSS OIL FREE AIR COMPRESSOR, AIR TANK 50L

High quality two-engine oil-free air compressor. High air efficiency. Low vibration. Low noise level. Overheat protection. Air efficiency: at 8 bar - 200 L / min; at 4 bar - 290 L / min. Capacity - 50 L. Weight - 50 kg.

- Air efficiency: at 8 bar - 200 l / min
- Air efficiency: at 4 bar - 290 l / min
- Capacity: 50 l
- Weight: 50 kg

Code	Packaging
2-1450X2F50	1 pc



GLOSS OIL FREE AIR COMPRESSOR, AIR TANK 100L

High quality single engine oil-free air compressor.
High air efficiency. Low vibration. Low noise level.
Overheat protection.

19

- Air efficiency: at 8 bar - 300 l / min
- Air efficiency: at 4 bar - 435 l / min
- Capacity: 100 l
- Weight: 91 kg

Code	Packaging
2-1450X3F100	1 pc



GLOSS MASKING FILM

All Purpose antistatic HDPE masking film to protect from dust, paint, dirt and moisture.

GLOSS MOISTURE ABSORBING MASKING FILM

Moisture Absorbing masking film - Breathable Masking Film is moisture-absorbent, allowing users to mask damp surfaces while reducing ghost marking after baking.



Code	Dimension	Packaging
GP 45705	4,5 x 7 m x 6 μm	35 pcs



Code	Dimension	Packaging
GL KMR9	5 x 100 m x 14 μm	1 roll



GLOSS MASKING FOIL

HDPE film is transparent, facilitating easy cutting at the edge of the painting surface. It is electrostatically loaded for fast adhesion to the surface, preventing small particles from reaching unprotected areas.

21

Code	Dimension	Packaging
GL KMR1	4 x 150 m x 10 µm	1 roll
GL KMR2	4 x 300 m x 10 µm	1 roll
GL KMR4	5 x 100 m x 10 µm	1 roll
GL KMR6	6 x 100 m x 10 µm	1 roll



22

GLOSS BITUMEN FILM BF18

Self-adhesive soundproofing film made from top-notch polymer-modified bitumen and special fillers. This flexible film easily adapts to curves, making it a breeze to apply. Ideal for reducing noise on thin sheet metal. It's perfect for both sound deadening and absorbing structure-borne noise.



Code	Dimension	Packaging
0009260	1000 x 500 x 1,7 mm	1 pc

GLOSS SELF-ADHESIVE POLYURETHANE COATING

High-performance foam is designed to effectively block out noise and regulate temperature. With its easy-to-apply self-adhesive backing, installation is hassle-free, ensuring quick and efficient usage such as engine hoods or other car parts.



Code	Dimension	Packaging
0004813	1020 x 500 x 10 mm	1 pc



GLOSS SYNTETIC CAR CARE CLOTH

Durable cloth for drying wet surfaces. The car care cloth is suitable for drying off wet car bodies, chrome, plastic and glass surfaces. It is also effective for cleaning car upholstery and interior panels, leaving no water residues or streaks. Its antibacterial treatment helps prevent odours.

23

Code	Dimensions	Packaging
CCC 4450	440 x 500 mm	1 pc





UAB HELVINA

Parko str. 96, Ramučiai
Kaunas distr. LT-54464, Lithuania
Tel. +370 37 308901
Fax +370 37 308902
E-mail: info@helvina.lt

