





2024
Catalogue

CAR BODY PREPARATION FOR PAINTING	MASKING	PROTECTIVE COATINGS	AUTOMOTIVE GLASS INSTALLATION, CAR BODY SEALING	PAINTING, VARNISHING	AEROSOLS	CLEANING, PROTECTION	POLISHING
3 PUTTY 12 FILLER 18 ABRASIVE PRODUCTS 22 TOOLS	30 MASKING TAPE 38 MASKING MEANS 40 TOOLS	43 UNDERBODY COATINGS 47 CAVITY PROTECTION 48 SAUNDPROOF PANELS 48 TOOLS	50 GLUE 51 SEALANTS 55 PLASTIC REPAIR	59 READY MIXED PAINTS 61 CLEARCOATS 65 HARDENERS 67 THINNERS 70 ADDITIVES FOR PAINTS 71 AUXILIARY MATERIALS 81 SPRAY STANDS 87 SPRAY BOOTH 89 DRYING EQUIPMENTS	92 PAINTS 97 PRAIMER 99 PUTTY 100 VARNISHES	102 CLEANING 103 PROTECTION	105 POLISHING PASTE 107 TOOLS






SOLL NITRO

Fast drying one component fine putty on nitro-cellulose-synthetic resin basis. Very well suited as spot filler to remove small damages such as scratches or stone pitting and to smooth minor irregularities.





SOLL ULTRA LIGHT Ught putty Palengyintas glaistas SOLL ULTRA LIGHT

leichtspachtel

SOLL ULTRA LIGHT

High quality lightweight polyester filler

for small and large areas. Easy to apply,

elastic, can be spread over large areas

evenly and free from pores, easy to sand even after a longer period of time.

100:2-3



20 °C/ 4-5 min.



20 °C/ 20-30 min.



P100-240

Code	Color	Contents	Packaging
SG12 020	light grey	0,2 kg	24 pcs

Code	Color	Contents	Packaging
SG6 UL 100	white	11	10 pcs
SG6 UL 150	white	1,5	8 pcs

Light putty

Leichtspachtel

Palengvintas glaistas

PUTTY

SOLL LIGHT

Middle viscous polyester filling putty, supplied at 30 % reduced density. Easy to sand and apply, suitable for large areas. Do not use on aluminum and galvanized surfaces.





100:2



20 °C/ 4-5 min.



20 °C/ 20-30 min.



P80-280

Code	Color	Contents	Packaging
SG6 100	beige	11	6 pcs
SG6 150	beige	1,5	3 pcs

SOLL LIGHT BLUE

Lightweighted putty, very well workable. Intended for filling small and bigger disparities, for repairing internal surfaces of car parts. It has good adhesion on aluminium and zinc materials. Thanks to low density it is very well sandable.





100:3



23 °C/ 4-5 min.



23 °C/ 20-30 min.



Code	Color	Contents	Packaging
SG6 LB 100	light blue	11	6 pcs
SG6 LB 150	light blue	1,5 I	6 pcs
SG6 LB 300	light blue	3	2 pcs

PUTTY

SOLL UNI

Softpolyesterbodyfiller, suitable for filling holes and uneven spots, when repairing car body parts. Easy to apply, elastic, can be spread over large areas evenly and free from pores, easy to sand even after a longer period of time. When applying on vertical surfaces does not flow.







20 °C/ 4-6 min.



20 °C/ 20-30 min.



P80-240

Code	Color	Contents	Packaging
SG8 100	white	1 kg	8 pcs
SG8 180	white	1,8 kg	6 pcs


SOLL ALU

Polyester filling putty with aluminium dust designed to fill large and small irregularities. It is characterized by high mechanical strength, excellent resistance to high temperatures and flexibility. Easy to apply and process with coarse and fine sandpaper.









20 °C/ 16-18 min.



Code	Color	Contents	Packaging
SG9 020	silver-grey metallic	0,2 kg	24 pcs
SG9 050	silver-grey metallic	0,5 kg	12 pcs
SG9 100	silver-grey metallic	1 kg	10 pcs
SG9 180	silver-grey metallic	1,8 kg	10 pcs



SOLL FULL

Universal polyester filling putty designed to fill large and small surface irregularities. Easy to apply and process with coarse and fine sandpaper. It presents good flexibility and adhesion both to primed and unprimed surfaces.



100:2-3



20 °C / 4-5 min.



20 °C / 20-30 min. IR 4-6 min.

FINE



P80-320

SOLL FINE

Finishing polyester putty, recommended for the repairs of small areas and final scratches up before the primer application. Easy to grind with the small-grained abrasive paper, giving the smooth surface as the result.





20 °C / 5-6 min.



20 °C / 30-35 min. JR 4-6 min.



P120-320

Code	Color	Contents	Packaging
SG1 020	yellow	0,2 kg	24 pcs
SG1 050	yellow	0,5 kg	12 pcs
SG1 100	beige	1 kg	8 pcs
SG1 180	beige	1,8 kg	6 pcs

Code	Color	Contents	Packaging
SG11 020	white	0,2 kg	24 pcs
SG11 050	white	0,5 kg	12 pcs
SG11 100	white	1 kg	8 pcs


PUTTY


SOLL BLACK CARBON

High quality carbon fibre reinforced polyester putty, recommended for filling large dents and holes in vehicles, caravans and trailers. Large hardness with high elasticity. Extremely short hardening time. Very good sanding properties. Excellent adhesion to various metals and plastics.











P80-320

Elastic polyester putty especially developped for use to coatable plastic parts. Excellent adhesivity, high elasticity and easy to sand.







SOLL PLAST

100:2



20 °C/ 4-5 min. 20 °C/ 30 min.



P120-400

Code	Color	Contents	Packaging
SG10 100	black	1 kg	8 pcs
SG10 180	black	1,8 kg	6 pcs

Code	Color	Contents	Packaging
SG5 050	dark grey	0,5 kg	12 pcs
SG5 100	dark grey	1 kg	12 pcs

opray putty

Spritzfüller

^{Jurš}kiamas glaista

PUTTY



Spray putty intended for unification of surface between filled and no filled places, or for straightening of surface on car bodies. It is used for formation of equable layer of putty on whole car body, which is necessary before application of filler and subsequently upper paint. After hardening SOLL FILL provides equable layer, which is easily sand able and also stays hard, tough, resistant to bend, stroke and vibrations.



UN 3105

5-10 min.

100:3-4 Thinner 10%



2-3; HVLP / RP



20 °C / 1 h; 60 °C / 30 min.



P180-320

Code	Color	Contents	Packaging
SG4 120	white	1,2 kg	6 pcs

SOLL GLASS

Polyester putty reinforced with special cut fibreglass. Recommended for filling and reinforcing the surfaces affected by corrosion after cleaning them first. It is characterised by a very high adhesion to any type of surface and mechanical strength. It is easy to apply, process and sand.





100:2-3



20 °C/ 4-5 min.



20 °C/ 20-30 min.



Code	Color	Contents	Packaging
SG3 100G	green	1 kg	10 pcs
SG3 150G	green	1,5 kg	6 pcs
SG3 180G	green	1,8 kg	10 pcs

PUTTY


SOLL ECO

Polyester putty reinforced with specialcut fibreglass. Recommended for filling and reinforcing the surfaces affected by corrosion after cleaning them first. It is characterised by a very high adhesion to any type of surface and mechanical strength. It is easy to apply and process.





20 °C/ 4-5 min.







SOLL GLASS LIGHT

Lightweight polyester fiberglass putty with a specific weight of about 1,1 kg/l. Suitable for repair small holes and large areas. Fast drying, easy to sand, very short glass fibers. To be used for car repair, vehicle and machine construction, model making and boats.



100:2-3



20 °C/ 4-5 min.



20 °C/ 20-30 min.



Code	Color	Contents	Packaging
SG3 020E	green	0,2 kg	24 pcs
SG3 050E	green	0,5 kg	12 pcs

Code	Color	Contents	Packaging
SG3 010L	yellow	11	6 pcs

PUTTY





SOLL ULTRA GLAZE

Finishing polyester putty, recommended for the repairs of small areas and final scratches up before the primer application. Easy to grind with the small-grained abrasive paper, giving the smooth surface as the result.

100:2

20 °C/ 3-4 min.

20 °C/15-20 min. /60 °C/5-20 min.

P120-360



SOLL RESIN

SOLL RESIN designed for rapid repair of surface damage. Polyester resin has good adhesion to the surface and mechanically resistant. Can be sanded after hardening. It may be trowelable to achieve the required surface smoothness. Resistant to weathering, dilute acids, gasoline, lubricants and oil. Designed to repair car bodies, boats, yachts, camping trailers, also repairs polyester and wooden surfaces.

100:3

 \odot

20 °C/ 45 min.



Code	Color	Contents	Packaging
SG13 UG 100	green	11	6 pcs

Code	Contents	Packaging
SG7 050	0,5	12 pcs
SG7 100	1 kg	6 pcs
SG7 500	5 l (5,6 kg)	1 pc

SOLL FIBER

Cloth of glass fiber. In connection with polyester resin designed for repair of car bodyworks or damages of GRP-parts.



SOLL REP

Repair set SOLL REP designed for rapid repair of surface damage. Polyester resin has good adhesion to the surface and mechanically resistant. Can be sanded after hardening. It may be trowelable to achieve the required surface smoothness. Resistant to weathering, dilute acids, gasoline, lubricants and oil. Designed to repair car bodies, boats, yachts, camping trailers, also repairs polyester and wooden surfaces.



100:2



20 °C/ 25-30 min.



Code	Area weight	Contents	Packaging
SG7 05M	150 g/m ²	0,5 m²	20 pcs
SG7 05M300	300 g/m ²	0,5 m²	15 pcs
SG7 05M450	450 g/m²	0,5 m²	15 pcs

Code	Contents	Packaging
SG7 025	0,25 kg	12 pcs

FILLER



One component HS-quality acrylic filler, characterized by short drying time and good filling properties. The product has very good adhesion to various substrates.



20 °C/40 min; 60 °C/ 15 min.



30-50 s; 20 °C



2-3; 1,6-1,8 mm;



SOLL SF2

One component adhesive primer with active protection against corrosion, suitable for car metallic surfaces. Lead and chromate free. Dries quickly.



20 °C/1 h; 60 °C/ 30-40 min.



18-20 s; DIN 4 mm; 20 °C



1-2; 1,8 mm; 3-5 bar

Code	Color	Contents	Packaging
SF1 LG 08	light grey	0,8 I	6 pcs

HS Acrylic filler HS Akrilinis užpildas

HS Acrylfüller

Code	Color	Contents	Packaging
SF2-1	dark grey	1 kg	6 pcs

FILLER



SOLL SF3

Two component HS-quality, fast drying acryl filler with excellent filling properties. Good adhesion to a variety of surfaces, easy to sand. Comes with acrylic hardener SOLL FH3.



20 °C/ 3-5 h; 60 °C/ 30-40 min.



25-30 s; 20 °C



) 4:



2-3; 1,5-1,8 mm; 2 - 2,5 bar

Code	Color	Contents	Packaging
SF3 LG1	light grey	1,25 I / set	6 pcs
SF3 DG1	dark grey	1,25 l / set	6 pcs
SF3 B1	black	1,25 l / set	6 pcs
SF3 W1	white	1,25 I / set	6 pcs



SOLL RAPID

Very fast drying filler. It has got very good application properties - excellent levelling and filling. It is dedicated for fast and small repair. Excellent sanding properties without clogging of sanding paper. Gives corrosion protection and very good adhesion.



20 °C/ 2,5-3 h; 60 °C/ 15-20 min; IR 12-15 min.



25-30 s; DIN 4 mm; 20 °C



1-3; 1,5-2,2 mm



g) 4:′



P400-600 (dry) P800-1000 (wet)

Code	Color	Contents	Packaging
SFR G125	grey	1,25 I (with hard.)	12 pcs
SFR B125	black	1,25 I (with hard.)	12 pcs
SFR W125	white	1,25 I (with hard.)	12 pcs
SFR G450	grey	4,50 I (with hard.)	4 pcs
SFR B450	black	4,50 I (with hard.)	4 pcs
SFR W450	white	4,50 I (with hard.)	4 pcs

FILLER







SOLL SF4

Two component acrylic filler having a high solid content with a wide range of application possibilities. excellent filling properties, easy to sand and quick drying. Can be used "wet on wet".



20 °C/ 3-5 h; 60 °C/30-40 min.



25-30 s; DIN 4 mm; 20 °C



4:1



2-3; 1,5-1,8 mm; 2-2,5 bar

Code	Color	Contents	Packaging
SF4 DG1	dark grey	11	6 pcs
SF4 LG1	light grey	11	6 pcs
SF4 B3.785	black	3,785 I	4 pcs
SF4 DG3.785	dark grey	3,785	4 pcs

Code	Color	Contents	Packaging
SF4 LG3.785	light grey	3,785 I	4 pcs
SF4 W3.785	white	3,785 I	4 pcs
FH5 025	colorless	250 ml (hardener)	12 pcs
FH5 946	colorless	946 ml (hardener)	6 pcs

FILLER







SOLL SF5

Two-component HS-quality acrylic filler on the basis of acrylic resin. It has excellent filling properties as well as good adhesion to a variety of surfaces, easy to sand. Comes with acrylic hardener SOLL FH6.

 \odot

20 °C/4-6 h; 60 °C/30 min.



25-30 s; DIN 4 mm; 20 °C



5:1



2-3; 1,6-1,8 mm

Code	Color	Contents	Packaging
SF5 DG09	dark grey	0,9 I (with hard.)	12 pcs
SF5 LG09	light grey	0,9 I (with hard.)	12 pcs
SF5 B09	black	0,9 I (with hard.)	12 pcs
SF5 W09	white	0,9 I (with hard.)	12 pcs

Code	Color	Contents	Packaging
SF5 DG30	dark grey	3 I (with hard.)	4 pcs
SF5 LG30	light grey	3 I (with hard.)	4 pcs
SF5 B30	black	3 I (with hard.)	4 pcs
SF5 W30	white	3 I (with hard.)	4 pcs

FILLER



EP Hardener 1:2

EP Kietiklis 1:2

EP Härter 1:2







SOLL EP PRIMER

Two component epoxy primer with very good anti-corrosion coating durability, high protective and insulating properties. The coating adheres very well to various substrates, mechanically strong and flexible.



20 °C/ 12 h; 60 °C/ 60 min



20-22 s; DIN 4 mm; 20 °C



1-2; 1,2-1,6 mm



2:1

P400-500 (dry) P800-1000 (wet)

Code	Color	Contents	Packaging
S-EP 05G	grey	0,75 I (with hard.)	6 pcs
S-EP 05B	black	0,75 I (with hard.)	6 pcs
S-EP 1	grey	1,5 I (with hard.)	6 pcs
S-EP 1W	white	1,5 I (with hard.)	6 pcs

Color	Contents	Packaging
black	1,5 I (with hard.)	6 pcs
grey	7,5 I (with hard.)	1 pc
black	7,5 I (with hard.)	1 pc
white	7,5 I (with hard.)	1 pc
	black grey black	black 1,5 I (with hard.) grey 7,5 I (with hard.) black 7,5 I (with hard.)

FILLER

SOLL WP WASHPRIMER



Two-component reactive primer that does not consist of chromates. This product is used as a typical penetrating primer that enhances the adhesion of following coats. It exhibits superb corrosion resistance and is perfect for surfaces with difficult adhesion.



20 °C/ 20 min.



17-19 s; DIN 4 mm; 20 °C




2:1



(1-2; 1,2-1,4 mm; 3,5 bar.

Code	Color	Contents	Packaging
S-WP 1	grey-green	1,5 I (with hard.)	6 pcs
S-WP 05	grey-green	0,75 I (with hard.)	12 pcs

SOLL PLASTIC









20 °C/ 30-40 min.



20 °C/ 20 min.



2; 1,3-1,4; 2-2,5 bar.

Contents	Packaging
0,5 l	12 pcs
11	12 pcs
	0,5 I

ABRASIVE PRODUCTS

SOLL ABRASIVE CLOTH





SOLL NON-WOVEN ABRASIVE MATERIAL

Non-woven material for matting and scuffing the surface. This pad feature a thinner and very flexible structure and work great on corners and contoured surfaces. May be used wet or dry.



Code	Dimension	Grit	Description	Packaging
S-FAC	153 x 219 mm	fine	in sheets	10 pcs
S-VFAC	153 x 219 mm	very fine	in sheets	10 pcs
S-UFAC	153 x 219 mm	ultra fine	in sheets	10 pcs
S-FAC-R	100 mm x 10 m	fine	in rolls	1 pc
S-UFAC-R	100 mm x 10 m	ultra fine	in rolls	1 pc

Code	Dimension	Grit	Color	Description	Packaging
S-MT-FA4	115 x 230 mm	fine	red	in sheets	10 pcs
S-MT-UFC12	115 x 230 mm	ultra fine	grey	in sheets	10 pcs
SR-MT-FA4	100 mm x 10 m	fine	red	in rolls	1 pc
SR-MT-UFC12	100 mm x 10 m	ultra fine	grey	in rolls	1 pc

ABRASIVE PRODUCTS

SOLL SANDING FILM DISC

Velcro sanding discs on film backing.



Code	Dimension	Grit	Packaging
NFD15015	Ø 150 mm	P80 - P2000	100 pcs

SOLL SANDING PAPER DISC

Velcro sanding discs on paper backing.



150 mm	P80 - P2000	100 pcs
125 mm	P60 - P500	100 pcs
	150 mm 125 mm	








SOLL FOAM ABRASIVE DISCS

SOLL FOAM Abrasive disc has a foam layer and microreplication technology, the sanding minerals are evenly distributed over the surface. This creates a sanding result with a smooth matt finish. It is ideally suited for removing sanding scratches from the paint. It can be perfectly used for repairing and finishing the paint layer. Wet use only! It can be used both mechanically and manually.



Code	Dimension	Grit	Packaging	
SSF150-3000	Ø 150 mm	P3000	15 pcs	

Code	Dimension	Grit	Packaging
771	230 x 280 mm	P60 - P2500	50 pcs

SOLL WATERPROOF SANDING SHEETS

Waterproof sanding sheets.

ABRASIVE PRODUCTS

SOLL SANDING FOAM

Sanding paper on foam backing.



Code	Dimension	Grit	Packaging
SSF11525	115 x 125 mm x 25m	P180 - P800	1 pc



SOLL CLEAN AND STRIP DISC, HOLDER

Abrasive disc for paint and rust removal 150mm. The fastest way to remove paint layers from parts. Longer lasting than sanding discs.



Code	Color	Dimension	Packaging
SCD-B150	black	150 mm	1 pc
SCD-P150	purple	150 mm	1 pc
S-SDH	-	45 mm	1 pc



TOOLS





SOLL "ROLOC" DICS HOLDER, 45 MM

Disc holder for abrasives 50mm. Suitable for pneumatic and power tools.



Code	Dimension	Packaging
SDCR-45	45 mm	1 pc

SOLL VELCRO SELF STICK DISCS, 15 HOLES

SOLL "Velcro" self stick discs designed for sticking to the sanding disk holder (eg.: SOLL TWISTER or SOLL WINNER), instead of the already-worn down disk.



Code	Dimension	Packaging
SSD-150-15	Ø 150 x 15 mm	50 pcs

TOOLS



SOLL INTERFACE PAD FOR SANDING DISCS

SOLL Interface Pad is an extra soft pad for universal sanding pads for use of Velcro abrasive discs. Through the outstanding adaptability of SOLL Interface Pad, the best possible finish is achieved without penetration of filler material even on rounded off surfaces, edges and sharp corners.

SOLL WINNER VELCRO SANDING PAD

15 and 21 holes sanding pads with "Velcro", backing system, which are ideally used for coarse, as well as, intermediate and final sanding.



Code	Description	Packaging
SSPW-150-15	15 holes	1 pc
SSPW-150-21	21 holes	1 pc
SAS 26	15 holes	1 pc

TOOLS



SOLL SANDING PAD HALF-ROUND

This pad is suitable for hand sanding with 150 mm grip discs. They can be used both with net and paper discs. The hand pad has a rounded edge, which makes it easy to sand hard to reach areas and rounded profiles.







SOLL SANDING HANDBLOCK, 22 HOLES

Sanding hand-block is a manual hand sanding tool for coarse, intermediate and final sanding of critical paint work. Through the sanding plate with integrated suction vents, it is perfect for the sanding of small, medium and large surfaces with considerably lowered MAK-values at the work place.



Code	Dimension	Packaging
SSB-70198	70 x 198 mm	1 pc

TOOLS

SOLL FOAM SANDING HANDBLOCK

This ergonomic hand sanding block has a indented grip which is sized to fit the hand. It is designed for 150mm sanding discs.



SOLL SANDING HANDBLOCK, 53 HOLES

Sanding hand-block is a manual hand sanding tool for coarse, intermediate and final sanding of critical paint work. Through the sanding plate with integrated suction vents, it is perfect for the sanding of small, medium and large surfaces with considerably lowered MAK-values at the work place.







Code	Discription	Dimension	Packaging
SSBF-70400	regulable	70 x 400 mm	1 pc
SSB-70400	not regulable	70 x 400 mm	1 pc



TOOLS

SOLL SANDING HANDBLOCK VELCRO

Handblock is used for leveling of large surfaces. Also it is used together with velour backed abrasives - hook and loop systems. Abrasive sheet size 70X400 mm.

SOLL SANDING BLOCK

The blocks are made of special rubber. Nine block sizes allow adjustments to the shape of the surface subject.



Code	Dimension	Packaging
SOLL 70400	70 x 400 mm	1 pc

Code	Dimmension	Packaging
B140/75	70 x 140 mm	1 pc
A210/75	70 x 210 mm	1 pc
D290/70	70 x 290 mm	1 pc
E135/75	70 x 135 mm	1 pc
C135/45	70 x 135 mm	1 pc

	Code	Dimmension	Packaging
-	A1Z 210/75	70 x 140 mm	1 pc
-	D1Z 290/70	70 x 210 mm	1 pc
•	C1 135/55	70 x 290 mm	1 pc
-	F 135/75/42	70 x 135 mm	1 pc
-			

TOOLS

SOLL CORK SANDING BLOCK

The cork sanding block is made of compressed fine granulated natural cork. The sanding block is equipped with sharp edges, in order to facilitate accurate sanding, even in corners. The plane surface is best suited for plane sanding in order to maintain the shape of an object.



Code	Dimension	Packaging	
SCBN	115 x 60 x 25 mm	200 pcs	



SOLL PAD FOR SMART ERASER

Smart eraser pad for pinstripe removal.



Code	Discription	Packaging
SP-6634	Smooth	1 pc
SP-6634P4	Pinion	1 pc
S-AD	(adapter)	1 pc

TOOLS

SOLL HOSE

Flexible air hose with adapter.



Code	Dimension	Packaging
SAH-21-4	4 m x ø21 mm	1 pc

SOLL TANK CLEAN SPATULAS

Thanks to the solvent (or the water) inside of the tank and the friction between the spatula and the abrasive sheet, you get the removal of the filler even if it is dry.



Code	Dimension	Packaging
S-GP	110 x 160 x 140 mm	1 pc



MASKING TAPE

SOLL GREEN 80

Suitable for all masking applications and light automotive use. Temperature resistant up to 80 °C.



Code	Dimension	Packaging
SOLG1850	18 mm x 50 m	48 pcs
SOLG2450	24 mm x 50 m	36 pcs
SOLG3650	36 mm x 50 m	24 pcs
SOLG4850	48 mm x 50 m	24 pcs



SOLL ORANGE

High-quality, self-adhesive painting tape, due to special glue and crepe paper, adheres perfectly to plastic, metal and painted surfaces. Resistant to temperatures up to +80 °C.



Code	Dimension	Packaging
SOLO2445	24 mm x 45 m	36 pcs
SOLO3045	30 mm x 45 m	30 pcs
SOLO3645	36 mm x 45 m	24 pcs
SOLO4845	48 mm x 45 m	18 pcs

SOLL CAR TAPE 60

Saturated semi crepe paper masking tape coated with solvent based natural rubber adhesive. Suitable for all masking applications and light automotive use. Temperature resistant up to 60 °C.



Code	Dimension	Packaging
SOLL401845	18 mm x 45 m	48 pcs
SOLL402445	24 mm x 45 m	36 pcs
SOLL403645	36 mm x 45 m	24 pcs
SOLL404845	48 mm x 45 m	18 pcs

SOLL CAR SPECIAL 90

Slightly creped high-performance masking tape for professional car refinishing with excellent tape to tape adhesion. Temperature resistant up to 90 °C.



Code	Dimension	Packaging
SOLL1845	18 mm x 45 m	48 pcs
SOLL2445	24 mm x 45 m	36 pcs
SOLL3645	36 mm x 45 m	24 pcs
SOLL4845	48 mm x 45 m	18 pcs

MASKING TAPE

SOLL WATERPROOF 100

Slightly creped high-performance masking tape for professional car refinishing with excellent tape to tape adhesion. Temperature resistant up to 100 °C. Perfectly suitable for water-based paints.



Dimension	Packaging
18 mm x 45 m	48 pcs
24 mm x 45 m	36 pcs
36 mm x 45 m	24 pcs
48 mm x 45 m	18 pcs
	18 mm x 45 m 24 mm x 45 m 36 mm x 45 m



SOLL DOUBLE SIDED ACRYLIC TAPE

Double sided acrylic tape with very high adhesive strength. Specialy designed for heavy trim, signs, strengtheners, etc. Good adhesion to metal, glass and most plastics. Solvent resistant.



Code	Dimension	Packaging
SAJ651	6 mm x 5 m x 1 mm	1 pc
SAJ951	9 mm x 5 m x 1 mm	1 pc
SAJ1251	12 mm x 5 m x 1 mm	1 pc

MASKING TAPE



SOLL DOUBLE SIDED TAPE

Double sided PE foam tape with high adhesive strength. Very good adhesion to clear coating and plastics. Excellent for fitting trims, signs, etc. Weather resistant, suitable for long term out door use. Solvent resistant.



Code	Dimension	Packaging
SDJ610	6 mm x 10 m	1 pc
SDJ910	9 mm x 10 m	1 pc
SDJ1210	12 mm x 10 m	1 pc
SDJ1910	19 mm x 10 m	1 pc
SDJ2510	25 mm x 10 m	1 pc

SOLL ORANGE FINE LINE MASKING TAPE

SOLL Orange Fine Line Tape is thinner and more translucent than other Fine Line Tapes making it ideal for seeing through to the painted surface. It is ideal for straight lines whilst also being highly flexible. Heat-resistant to temperatures up to 150 °C for at least 45 minutes; after painting, it can be cleanly removed leaving a defined line with no adhesive residue.



Code	Dimension	Packaging
S-OFLT1	1 mm x 55 m	10 pcs
S-OFLT1.5	1,5 mm x 55 m	10 pcs
S-OFLT2	2 mm x 55 m	10 pcs
S-OFLT3	3 mm x 55 m	10 pcs
S-OFLT6	6 mm x 55 m	10 pcs



MASKING TAPE

SOLL GREEN FINE LINE MASKING TAPE

It uses a thermally stablised PVC backing with a rubber based pressure sensitive adhesive. It is highly flexible, easy to curve and will hold and cleanly remove from surfaces in temperatures up to 132 °C for at least 30 minutes. After demasking, it will leave no residue and a sharp, clean separation line.



Code	Dimension	Packaging
S-FLT1	1 mm x 55 m	10 pcs
S-FLT1.5	1,5 mm x 55 m	10 pcs
S-FLT2	2 mm x 55 m	10 pcs
S-FLT3	3 mm x 55 m	10 pcs
S-FLT6	6 mm x 55 m	10 pcs
S-FLT9	9 mm x 55 m	10 pcs



SOLL PAINT PROTECTION FILM

It is used to protect the car body against small damages. Protects against: chips of stone, sand, gravel and rubble, dirt and dust, salt sprinkled on the roads in a winter time, scratches.



Code	Dimension	Packaging
SPF-3	100 mm x 3 m	1 pc


MASKING TAPE



SOLL BLACK MEDIUM FILM

Self-adhesive protective tape, which is used to protect window slats, parts of bumpers, thresholds, etc.







ADVANCED MASTER TAPE

It is ideal for painting processes, providing a great resistance to high temperatures up to 100 °C for 60 min. with a double adhesive positioning and an automatic rolled that allows to work easily by giving a quick and effective application. It allows to be manually cut both vertically and longitudinally, facilitating the user to have the desire sizes in order to mask the parts of the vehicle during its processes of painting. It also helps to mask rubbers and those inaccessible curved areas where you need a very flexible product.

Code	Dimension	Packaging
MT	75 mm x 20 m	1 pc

MASKING TAPE

SOLL TRIM MASKING TAPE

Adhesive tape designed to seal the rubber parts around the car glass before painting. Resistant to 100 °C. Suitable for use with water-based paint. Does not leave any adhesive residues. Resistant to chemicals. Suitable for all type of cars. Perforated, easily tear.

Code	Dimension	Packaging
STM4510	10-45 mm x 10 m	36 pcs

SOLL CLOTH TAPE

Universal cloth duct tape. Suitable for the temporary fitting of pipes, tubes and other temporary repairs. Weather resistant.



Code	Dimension	Packaging
SAR5025	50 mm x 25 m	30 pcs

SOLL FOAM MASKING TAPE

Universal round foam tape for gaps (e. g. door, boot, bonnet) up to 13 mm. Temperature resistance 1h/95 °C.





PERFECT FOAM MASKING TAPE

Thanks to the special "T" shape it adheres precisely to the different surfaces of any vehicle. Basically, the ideal masking solution for reducing masking time around doors, tailgates and other vehicle access points.

_	Code	Dimension	Packaging
	SPJ1320	13 mm x 20 m	1 pc
	SPJ1350	13 mm x 50 m	1 pc

Code	Dimension	Packaging
PFC	20 m	1 pc

MASKING FILM, MEANS



SOLL LOGOTAPE

Adhesive tape for re-fixing logos, emblems on to the panel.



Code	Dimension	Packaging
LOGOTAPE	50 x 300 mm	10 pcs

SOLL MASKING FOIL STANDART

Masking foil for fast and effective masking work.



Code	Dimension	Packaging
SP45005	4 x 5 m	50 pcs

MASKING MEANS



SOLL SELF ADHESIVE PROTECTION FILM

Self-adhesive film is created for temporary protection from external factors for broken windows, roof windows and damaged doors.



SOLL MASKING PAPER, LIGHT BROWN

Masking paper with excellent resistance to solvents, base coats and clear coats.

Code	Dimension	Packaging
S304760	60 cm x 100 m	1 roll

Code	Dimension	Packaging
300 50	40 g/m² 300 mm x 50 m	1 roll
600 50	40 g/m² 600 mm x 50 m	1 roll
900 50	40 g/m² 900 mm x 50 m	1 roll
300 40	40 g/m² 300 mm x 300 m	1 roll
600	40 g/m² 600 mm x 300 m	1 roll
900	40 g/m² 900 mm x 300 m	1 roll
1200	40 g/m² 1200 mm x 300 m	1 roll

TOOLS

SOLL MASKING FILM CUTTER

Knife for masking film.





Code	Packaging
S-CUT	100 pcs

SOLL DISPENSER

Stend construction enables to fix four dimension rolls of paper for masking (30 cm, 60 cm, 90 cm, 120 cm) and one dimension roll of foil masking.



Code	Packaging
SOLL 114	1 pc

S 1 | TOOLS |





UNDERBODY COATINGS



SOLL ANTIGRAVEL

Antistone-chip texturized deadening protective coating based on rubber and resins in solvent. Fast drying and excellent protection against rust. Especially suitable for visible car parts. It gives a matt, textured surface. Can be covered with all types of paint.

Code	Color	Contents	Packaging
S700300	black	1 kg	12 pcs
S700301	white	1 kg	12 pcs
S700302	grey	1 kg	12 pcs
S700307	black	2 kg	12 pcs
S700308	white	2 kg	12 pcs
S700309	grey	2 kg	12 pcs

www.sollpaints



UNDERBODY COATINGS







SOLL ANTIGRAVEL SPRAY

An overcoatable under-body coating aerosol spray based on synthetic resins and rubbers. Designed for the protection of gravel and pebble strokes. Fast drying and excellent protection against rust. Particularly suitable for visible car parts. It gives a matte, textured surface, which is easy to over-paint.



SOLL UNDERBODY COATING

Based on bitumen. This product gives excellent and durable protection against rust and stone chip and has sound deadening properties. Not over-paintable. It creates a strong, elastic, thermo-insulating layer, which protects against weathering.



Code	Color	Contents	Packaging
SU B500	black	500 ml	12 pcs
SU W500	white	500 ml	12 pcs
SU G500	grey	500 ml	12 pcs

Code	Color	Contents	Packaging
S700314	black	11	12 pcs

UNDERBODY COATINGS



SOLL UNDERBODY COATING

Based on bitumen. This product gives excellent and durable protection against rust and stone chip and has sound deadening properties. Not over-paintable. Developed as corrosion protective coating on metal surfaces, especially for application on cars, trailers, trucks, such as the under side of floor panels, the inside of wheel arches on parts of the chassis, ect. It creates a strong, elastic, thermo-insulating layer, which protects against weathering.





SOLL ANTIGRAVEL PLUS 2 IN 1

Over paintable anti gravel coating and seam sealer in one, with anti-corrosion and sound-deadening properties based on rubber and resins. After drying the product is over paintable with all conventional paint systems. After the product has completely dried remains a durable elastic film that offers a good protection against various climates and gravel.

_	Code	Color	Contents	Packaging
_	S700211	black	500 ml	12 pcs

Code	Color	Contents	Packaging
S700310	grey	11	12 pcs
S700311	black	11	12 pcs

UNDERBODY COATINGS





SOLL BITUMEN UNDERBODY COATING

It is used for anti-corrosion protection of car bottoms, fenders and noise protection.

Code	Discription	Contents	Packaging
S700317	not overcoatable	1 kg	6 pcs
S700318	not overcoatable	5 kg	1 pc

CAVITY PROTECTION



SOLL BODY CAVITY PROTECTION

It is a very penetrative and reliable anti-corrosion coating that displaces moisture, even in difficult to reach places. Designed for applying on new and used car closed cavities and hard to reach areas (sills, doors, etc.). Apply the coating on a clean and dry surface. After drying, it forms long, waxy film with long term corrosion protection.



SOLL BODY CAVITY PROTECTION SPRAY

It is a very penetrative and reliable anti-corrosion coating in aerosol that displaces moisture, even in difficult to reach places. Designed for applying on new and used car closed cavities and hard to reach areas (sills, doors, etc.). Apply the coating on a clean and dry surface. After drying, it forms long, waxy film with long term corrosion protection.

Code	Color	Contents	Packaging
S700315	tranparent	11	12 pcs
S700316	brown	11	12 pcs


Code	Color	Contents	Packaging
S700212	brown	500 ml	12 pcs
S700213	transparent	500 ml	12 pcs

SOUNDPROOF PANEL, TOOLS

5

SOLL SELF-ADHESIVE SOUNDPROOF PANEL

Self-adhesive bituminous mat with high silencing and elasticity capabilities, enables optimal matching the shape of surface. Designed for silencing floor, cockpit and boot, and for shaping acoustical space of car interior. In wavy and smooth.



SOLL UNDERBODY SPRAY GUN

Spray gun designed for the application of soundproofing, gravel protection and bituminous / wax-based rust proofing and undercoating. The gun has a threaded collar which allows for direct attachment to standard one liter cans. As an option a plastic wand can be supplied for the spraying of wax-based rust proofing in cavities, hollow beams, doors, ect.

Code	Packaging
SC-5514	1 pc



GLUE



SOLL SP 11

An excellent, non-sag, one-component, flexible and high performance polyurethane adhesive that cures on exposure to atmospheric moisture to form a tough, durable adhesive. Completely solvent free. It is odourless and also non conductive allowing the correct bonding to glass incorporating radio antenna or additional electrical equipment. Drive away time: 3 hours (23 °C and 50 % relative humidity).



SOLL SP 15

One-component, ultra fast-curing, flexible and high performance polyurethane adhesive for the bonding of vehicle glass-direct glazing. It is specifically designed to give a fast and safe drive-away time on vehicles fitted with airbags. Particularly fast skinning and curing times. Drive away time: 2 hour (23 °C and 50 % relative humidity).

Code	Color	Contents	Packaging
SP 11	black	310 ml	12 pcs
SP 01 15	black	15 ml (primer)	1 pc
SP 01 30	black	30 ml (primer)	1 pc

310 ml	12 pcs
15 ml (primer)	1 pc
30 ml (primer)	1 pc
	15 ml (primer)

SEALANTS



SOLL SP 18

One-component, ultra fast-curing, flexible and high performance polyurethane adhesive for the bonding of vehicle glass-direct glazing. It is specifically designed to give a fast and safe drive-away time on vehicles fitted with airbags. Particularly fast skinning and curing times. Drive away time: 1 hour (23 °C and 50 % relative humidity).



SOLL SP 5

One component, very fast curing, polyurethane elastic adhesive / sealant designed for car body sealing which cures on exposure to atmospheric moisture. Suitable for sealing, seam sealing, simple bonding as well as for vibration reduction and sound deadening measures in crash body repair and car body construction. It is characterised by an initial controlled viscosity that makes the product easy to brush and to smooth, particularly in those applications where a thin layer or bead of adhesive is required.

Code	Color	Contents	Packaging
SP 18	black	310 ml	12 pcs
SP 01 15	black	15 ml (primer)	1 pc
SP 01 30	black	30 ml (primer)	1 pc

Code	Color	Contents	Packaging
SP5 310W	white	310 ml	12 pcs
SP5 310G	grey	310 ml	12 pcs
SP5 310B	black	310 ml	12 pcs
SP5 310Y	yellow	310 ml	12 pcs



SEALANTS




SOLL SP 6

One component, MS polymer elastic sprayable sealant. Free of isocyanates, phtalates, silicone, PVC and solvents. Fast drying and good adhesion to most hard and elastic surfaces. Excellent weathering resistance. Over-paintable.



Color	Contents	Packaging
grey	290 ml	12 pcs
beige	290 ml	12 pcs
black	290 ml	12 pcs
	grey beige	grey 290 ml beige 290 ml







Code	Color	Contents	Packaging
ST 085	grey	850 g	12 pcs

SEALANTS

SOLL SEAM SEALING TAPE

self-adhesive butyl-based The hermetic tape is intended for lamp repair, sealing of door edges.



Code	Dimension	Packaging
SSJ4	4 mm x 9,14 m	1 roll
SSJ8	8 mm x 4,5 m	1 roll

SOLL PNEUMATIC GUN



Code	Packaging	
SPG	1 pc	



SOLL CAULKING GUN

SOLL Sealant gun, suitable for 290-310 ml tubes with glue or silicone.



Code	Discription	Packaging
SCG 11	red	12 pcs
SCG 21	black	24 pcs

SOLL CAULKING GUN NOZZLE

Plastic nozzle for adhesives and sealants.




Code	Packaging	
SSB 03	1 pc	

SEALANTS, PLASTIC REPAIR November 1987

SOLL BRUSH

Brush for seam sealant.







SOLL POLYURETHANE ADHESIVE

SOLL 2K PU-Adhesive for plastics parts, supplied with two cappings (PKA). Drying time 1 or 5 min.

Code	Drying time	Contents	Packaging
SPU 50 1M	1 min	50 ml	12 pcs
SPU 50 5M	5 min	50 ml	12 pcs
PKA		-	12 pcs

PLASTIC REPAIR

SOLL MANUAL GUN FOR THE APPLICATION OF 50 ML CARTRIDGES

SOLL manual gun for the application of 50ml cartridges.



Code	Packaging	
SCG 53	1 pc	


SOLL MANUAL GUN FOR POLYURETHANE ADHESIVE

Manual gun for the application of 50ml cartridges.



Packaging	
1 pc	

PLASTIC REPAIR





SOLL ALUMINIUM MESH

An aluminium netting is intended for the repair of car bumpers and other plastic parts. Used with a soldering tool. Netting size 200 x 250 mm.

Code	Dimension	Packaging
SAM 200250	200 x 250 mm	10 pcs



SOUL READY MIXED PAINTS Noo-string dilose was

SOLL COLOUR FAN

The color fan contains a selection of the most common ready mix colors. All colors are numerically sorted with reference to their brands. All colors shown in this fan are reproductions. They should only be hints for identifying the colors.





SOLL BP

One component structural bumper paint, resistant to +70 °C temperature, suitable for the repair work on plastic surfaces likely to be found in automotive industry such as bumpers, trims (skirting), outside mirrors, etc. Direct adhesion on cleaned and sanded plastic such as ABS, ABS-PC, PP-EPDM, against weathering are the most distinguishing marks of this product.



20 °C/ 20 min.; dust dry 20 °C/ 60 min.; set to touch



20-25 s; DIN 4 mm; 20 °C



) 2; 1,6-1,8 mm; 3-5 bar

Code	Color	Contents	Packaging
SBP 05B	black	0,5	3 pcs
SBP 1B	black	11	6 pcs

READY MIXED PAINTS



SOLL AC

Ready to use high quality automotive acrylic paint. Weather-resistant, does not lose luster and colour intensity. Well-distributed and adhesion to the surface, making it suitable for full or partial painting of cars and trucks.

2:1 with Acrylic hardener

20-22 s; DIN 4 mm; 20 °C



2 1/2; 1,3-1,4 mm; 3-5 bar



20 °C/5-6 h; 60 °C/25-30 min.



SOLL BC

Ready to use high quality automotive base coat paint with "metal" effect. Well-distributed and adhesion to the surface, making it suitable for full or partial painting of cars and trucks. Can be recoatable with 2K acrylic clearcoats



2:1 with Basecoat thinner



16-18 s; DIN 4 mm; 20 °C



2-3; 1,3-1,4 mm; 3-4 bar



20 °C/ 5-10 min.

Packaging
3 pcs

Code	Contents	Packaging
SB	11	3 pcs

CLEARCOATS



SOLL 2.1 VOC

It is the high quality transparent twocomponent acrylic clearcoat with high content of solids. It provides a hard, high-gloss, scratch-resistant surface and excellent appearance. 2.1 VOC and USA National Rule Compliance.

20 °C/ 4-6 h; 60 °C/ 30-40 min.

14-16 s; DIN 4 mm; 20 °C



2; 1,2-1,3 mm; 2 bar

Code	Description	Drying	Contents	Packaging
C 2.1 100	Clearcoat	-	11	6 pcs
C 2.1 500	Clearcoat	-	51	4 pcs
H 2.1 050S	Hardener	slow	0,5 I	6 pcs
H 2.1 250S	Hardener	slow	2,5 I	4 pcs
H 2.1 050N	Hardener	normal	0,5 I	6 pcs
H 2.1 250N	Hardener	normal	2,5 l	4 pcs
H 2.1 050F	Hardener	fast	0,5 l	6 pcs
H 2.1 250F	Hardener	fast	2,5	4 pcs



SOLL UHS

It is the highest quality transparent twocomponent acrylic clearcoat with high content of solids. It provides a hard, high-gloss, scratch-resistant surface and excellent appearance. Since it is sufficient to spray 1,5 - 2 layers, spread evenly and dries quickly. Use with SOLL UHS 25 (normal) or SOLL UHS 10 (fast) hardener, depending on the conditions of use.



20 °C/ 12 h; 60 °C/ 30-35 min.



15-17 s; DIN 4 mm; 20 °C



2:1



1,5-2; 1,2-1,4 mm; 2-2,5 bar

Code	Contents	Packaging
C UHS 100	11	6 pcs
C UHS 500	5 I	4 pcs




CLEARCOATS



Transparent acrylic lacquer, designed for quick and high-quality results. Extremely fast drying: at + 20 degrees temperature dries in 3 hours; at + 60 degrees temperature dries in 10 minutes. Suitable for all car varnishing.








16-17 s; DIN 4 mm; 20 °C



1,5-2; 1,2-1,3 mm;





SOLL C1

Fast drying and high gloss clear coat. It may be also very easily sanded as well as polished to eliminate possible imperfections. Because of its hardness, high gloss, UV resistance and resistance to all climatic conditions to ensure a good appearance and stable layer. Use with hardeners SOLL H1 10 (fast) and SOLL H1 25 (normal).



20 °C/ 12 h; 60 °C/ 30 min.



16-17 s; DIN 4 mm; 20 °C



2:1 (thinner 0-10 %)



1,5-2; 1,3-1,4 mm; 2-2,5 bar

Code	Contents	Packaging
C1 1	11	12 pcs
C1 5	5	4 pcs

SOL

CLEARCOATS

SOLL C2

Acrylic clear coat with high levels of solid particles. Because of its hardness, high gloss, UV resistance and resistance to all climatic conditions to ensure a good appearance and stable layer. Since it is sufficient to spray one and a half layer, spread evenly and dries quickly.



) 20 °C/ 10 h; 60 °C/ 30 min.




s) 16-17 s; DIN 4 mm; 20 °C



2:1 (thinner 0-6 %)



2; 1,3-1,4 mm; 2-2,5 bar



SOLL C3

Hardness, high gloss, UV stability and weather resistance guarantee excelent appearance and durability of the coat. Good flow and fast drying ensures effortless repair and short time of staying in spray booth. Is compatible with all basecoats available on the market.



20 °C/ 10 h; 60 °C/30 min.



)s) 16-17 s; DIN 4 mm; 20 °C



1) 2:1 (thinner 0-5 %)



2; 1,3-1,4 mm; 2-2,5 bar

Code	Hardener	Drying	Contents	Packaging
C3 1N	H3 25	normal	1,5 I (with hardener)	12 pcs
C3 5N	H3 25	normal	7,5 I (with hardener)	4 pcs
C3 1G	H3 10	fast	1,5 I (with hardener)	12 pcs
C3 5G	H3 10	fast	7,5 I (with hardener)	4 pcs

H3 10

01

2,51



CLEARCOATS



SOLL C4

Clearcoat has a very good flow and resistance to UV rays and weathering. It is characterized by a good gloss and high ease of application and perfectly polished. It is a perfect economic solution, because a very low price qualifying this clearcoat to group of ECONOMIC products.

20 °C/ 10 h; 60 °C/ 30 min.

Matt clearcoat Matinis lakas Klarlack Mat



16-17 s; DIN 4 mm; 20 °C




2:1 (thinner 0-5 %)



2; 1,3-1,4 mm; 2-2,5 bar

C4 15N H4 25 normal 1,5 I (with hardener) 12 pcs C4 75N H4 25 normal 7,5 I (with hardener) 4 pcs C4 06F H4 10 fast 0,6 I (with hardener) 12 pcs C4 15F H4 10 fast 1,5 I (with hardener) 12 pcs	Code	Hardener	Drying	Contents	Packaging
C4 75N H4 25 normal 7,5 I (with hardener) 4 pcs C4 06F H4 10 fast 0,6 I (with hardener) 12 pcs C4 15F H4 10 fast 1,5 I (with hardener) 12 pcs	C4 06N	H4 25	normal	0,6 I (with hardener)	12 pcs
C4 06F H4 10 fast 0,6 I (with hardener) 12 pcs C4 15F H4 10 fast 1,5 I (with hardener) 12 pcs	C4 15N	H4 25	normal	1,5 I (with hardener)	12 pcs
C4 15F H4 10 fast 1,5 I (with hardener) 12 pcs	C4 75N	H4 25	normal	7,5 I (with hardener)	4 pcs
	C4 06F	H4 10	fast	0,6 I (with hardener)	12 pcs
CA 755 LIA 10 feet 7.5 L (with hardener) 4 nos	C4 15F	H4 10	fast	1,5 I (with hardener)	12 pcs
C4 / OF FIG. 10 last 7,5 I (with hardener) 4 pcs	C4 75F	H4 10	fast	7,5 I (with hardener)	4 pcs

SOLL MC





20 °C/ 10 h; 60 °C/ 30 min



17-18 s; DIN 4 mm; 20 °C



2:1



2; 1,3-1,4 mm; 2-2,5 bar

Code	Hardener	Drying	Contents	Packaging
MC 15N	MH 25	normal	1,5 I (with hardener)	12 pcs

SOLHARDENERS

SOLL UHS HARDENER

Acrylic hardener intended to use with acrylic clearcoat SOLL UHS.



Code	Drying	Contents	Packaging
H UHS25 050	normal	0,5 I	6 pcs
H UHS25 250	normal	2,5	4 pcs
H UHS10 050	fast	0,5 I	6 pcs
H UHS10 250	fast	2,5	4 pcs

SOLL AIR DRY HARDENER

Universal acrylic hardener is intended for use in the automotive industry with acrylic products.





Code	Drying	Contents	Packaging
H AD25 050	Normal	0,5	12 pcs
H AD25 250	Normal	2,5 I	4 pcs



HARDENERS

SOLL H1

Acrylic hardener intended to use with 2K HS Acrylic clearcoat SOLL C1.



Code	Drying	Contents	Packaging
H1 25 05	normal	0,5 l	12 pcs
H1 25 25	normal	2,5	4 pcs
H1 10 05	fast	0,5 l	12 pcs
H1 10 25	fast	2,5	4 pcs

SOLL UNI

Universal acrylic hardener is intended for use in the automotive industry with acrylic products.





Code	Drying	Contents	Packaging
UNI 25 05	Normal	0,5 l	6 pcs
UNI 10 05	Fast	0,5	6 pcs

HARDENERS, THINNERS

SOLL FH5

"Extra fast" acrylic hardener SOLL FH5 is intended to use with acrylic filler SOLL HS 4+1 SF4.

SACRYLIC hardener SOLL HS 4+1 SF4.

SACRYLIC hardener SOLL FH5

ACRYLIC HARDEN H5

ACRYLIC H5

Code	Contents	Packaging
FH5 025	250 ml	12 pcs
FH5 946	946 ml	6 pcs



SOLL ACRYL

Acrylic thinner SOLL ACRYL used to dilute all acrylic products.

Code	Contents	Packaging
AC 1	11	12 pcs
AC 5	51	4 pcs

THINNERS



Code	Contents	Packaging
BC 1	11	12 pcs
BC 5	5 I	4 pcs



SOLL SIL

SOLL SIL is used to remove silicone from surfaces before painting. It helps quickly and completely remove variety of contaminations such as lubricants, oils, silicones and others.

Contents	Packaging
11	6 pcs
51	4 pcs
	Contents 1 I 5 I

SOL THINNERS THINNERS



SOLL SIL (SLOW)

Used to remove silicone from surfaces which are prepared to paint. It helps quickly and completely remove lubricants, oils, silicones and other contamination from the surface.

Code Contents Packaging SIL 1S 1 I 12 pcs SIL 5S 5 I 4 pcs

SOLL NITRO 646

Thinner NITRO 646 designed to wash tools and to dilute the nitro paints, varnishes and putties to meet required operating viscosity.



Code	Contents	Packaging
STN1 010M	11	20 pcs
STN1 050	5 I	1 pc
STN1 200	20 I	1 pc
STN1 200	20	1 pc

ADDITIVES FOR PAINTS



The drying time of 2K polyurethane paints and all acrylic products is much accelerated through the addition of the SOLL EXPRESS. In winter time at low temperatures the use of this additive is especially recommended. Attention: the pot life is also reduced.



SOLL ELASTIC

Additive for paints and clearcoats that enhances flexibility. Painting exposed to the impact of stones does not flake. The use in paints prevents cracking due to excessive hardness and lack of flexibility. It is also used as an additive to paints, which correspond to elements made of plastic. By increasing the flexibility of the coating prevents the formation of cracks and chipping paint on the flexible body parts exposed to strain.

Palestan	d refrishing	XPA	E99
) D	rying ad Žiūvimo	celera	tor
Troc	knungs	beshle	uniger
	viiniids	Desnie	

Code	Contents	Packaging
S-EXP 05	500 ml	12 pcs

Code	Contents	Packaging
S-EL 1	11	12 pcs

ADDITIVES FOR PAINTS, AUXILIARY MATERIALS

SOLL LÖSER



It is used to reduce differences created by the confluence of old and newly located coating of acrylic lacquer. Do not use to eliminate such places on the base, metal and pearl lacquers.



Code	Contents	Packaging
S-LOS 05	0,5 I	12 pcs
S-LOS 1	11	12 pcs



SOLL PAINT TOUCH-UP DROPPER

Paint dropper bottle of clear plastic for paint touch ups, contains of stainless steel mixing ball and fine touch up paint brush integrated into lid. Fine steel tube for accurate paint placement.

Code	Contents	Packaging
STB-05-20	20 ml	100 pcs
STB-05	25 ml	10 pcs

SOLL PAINT TOUCH-UP BOTTLE

Plastic bottle with the brush for paints.



Code	Contents	Packaging
STB-02-20	20 ml	100 pcs
STB-02	30 ml	50 pcs



SOLL PAINT TOUCH-UP MICROBRUSH

Micro-soft touch-up tips for accurate retouching of small defects in paint work. Sets of 100 pcs.

Code	Packaging
STB 07	4 pcs



SOLL DUST NEEDLE SET

This dust needle set is an effective tool for removing lint, dirt and dust from wet paint. Sets of 10 pcs.



SOLL PAINT NOSE REMOVER

A dust file made of very hard metal for removal of dust and dirt from dried paint.



Code	Packaging	Code	Packaging
ONS 10	1 pc	SPNR	1 pc



State of the state



SOLL ALUMINIUM SCALED STRIP

SOLL Aluminium scaled strip for mixing 2K 2:1, 3:1, 4:1, 5:1.



SOLL PAINT MIXING PLASTIC STICK

Plastic mixer for manual mixing of enamels, base paints, primers, fillers and other liquid products.

Code	Packaging	
SPM 02	2000 pcs	

SOLL METAL SPRAY CARD

Primed metall card is special colour match card with which the best assesment of the spray sample can be tested prior to the coating process. Due to the black line, hiding power can also be tested easily. Primed metal card are suitable for colour matching conventional as well as water-based systems.



Code Dimension Packaging S-DKM 105 x 150 mm 100 pcs

METAL SPRAY CARDS

Med Gray

Dark Gray

100 sheets

SOLL NYLON STRAINER


For the fast and efficient straining of all solvent and water based paints.

Code	Description	Packaging
SDF 95	95 μm	1000 pcs
SDF 125	125 µm	1000 pcs
SDF 190	190 µm	1000 pcs

SOLL DEFECT GUIDE COAT

SOLL defect guide coat is intended for highlighting all filling imperfections on primers and masses. Product features: 1) instant defect detection; 2) no dry time required; 3) no masking required; 4) easy application; 5) perfect for dry sanding; 6) no solvents.





Defect guide coat Kontroliniai miltelia



SOLL SPRAYER

Compressed air sprayer. Designed for the filling of cleaning agents and silicone remover. Made of highly robust, silicone free, solvent resistant plastic.




Code	Description	Packaging
S-CAS	11	1 pc

S 0 L AUXILIARY MATERIALS = Nowwell-basints.com

SOLL RESISTANT 70

Wet wiping rag for the streak free application of silicone-remover prior to spraying. Solvent resistant, extremely tear resistant, reusable, lint-free and washable. Basis weight: 70 g/m².



RESISTANT 70


SOLL RESISTANT 70



Code	Dimension	Description	Packaging
S400102	36 x 32 cm	in rolls (500 wipes)	1 roll

SOLL RESISTANT 80 BLUE

Wet wiping rag for the streak free application of silicone-remover prior to spraying. Solvent resistant, extremely tear resistant, reusable, lint-free and



Code	Dimension	Packaging
S400201	36 x 40 cm	35 pcs

RESISTANT 80 Blue 35wipes

SOLL QUICK WIPES

Perforated cleaning paper for all kinds of maintenance. In roll 500 sheets.



Code	Dimension	Packaging
S400401	36 x 38 cm (2 layers)	2 rolls

S O L AUXILIARY MATERIALS AUXILIARY MATERIALS




Perforated cleaning paper for all kinds of maintenance. In roll 800 sheets.



SOLL ANTI DUST RAG WAVE

Universal GSI tack rag to be used for removal of dust before applying a new paint coat.



Code	Dimension	Packaging
S-CPR 800	25 x 26 cm (2 layers)	2 rolls

AUXILIARY MATERIALS

SOLL TACK CLOTH

Tack cloth with non-drying resin.



This sticky tack cloth applicable for conventional solvent - based, water - thinnable as well as for powder paint materials during the preparation of further painting.



Code	Dimension	Packaging
S8050	50 x 80 cm	100 pcs



Code	Dimension	Packaging
S4581	45 x 81 cm	50 pcs

SPRAY STANDS



Code Packaging

100 pcs

SGMK-12

SOLL 12 PCS SPRAY GUN MAINTENANCE KIT

SOLL spray gun maintenance kit. Kit contains 12 pcs.



SOLL 23 PCS SPRAY GUN MAINTENANCE KIT

SOLL spray gun maintenance kit. Kit contains 23 pcs.



Code	Packaging
SGMK-23	20 pcs

SPRAY STANDS



SOLL MAGNETIC SPRAY GUN HOLDER

Portable, as it attaches securely to spray booth walls, mixing rooms, tool boxes or anywhere that has a metal surface. The powerful magnet keeps it from sliding or tilting out of position when loaded. Includes a protective coating to prevent scratches on gun cups.



SOLL MAGNETIC SPRAY GUN HOLDER

Magnetic spray gun holder for two spray guns. Portable, as it attaches securely to spray booth walls, mixing rooms, tool boxes or anywhere that has a metal surface. The powerful magnet keeps it from sliding or tilting out of position when loaded. Includes a protective coating to prevent scratches on gun cups.





Code	Packaging	
SOLL 120	1 pc	

Code	Packaging	
SOLL 121	1 pc	

SPRAY STANDS SPRAY STANDS




SOLL SPRAY GUNS STAND

Single free-standing stand that enables pouring paints and lacquers into spray gun containers.

SOLL MULTI SPRAY STAND

The stand enables fastening the body element with the possibility of turning by 360°.

Code	Packaging	
SOLL 119	1 pc	



SPRAY STANDS



SOLL 110

SOLL X-STAND Sturdy metal bumper painting stand, X-shaped.


> Code **Packaging SOLL 112** 1 pc

1 pc

SPRAY STANDS

SOLL HEAVY DUTTY PANEL STAND

Metal folding car parts stand, with attachment at the bottom.



Code	Packaging	
SOLL 113	1 pc	

SOLL PANEL STAND



SPRAY STANDS



Sturdy steel bumper stand with wheels. Designed to hold 8 bumpers.



SOLL WHEEL MASTER PAINT STAND

Sturdy steel rim stand with wheels. Designed to hold 4 rims.

Code	Dimension	Packaging
SOLL 109	1,20m x 70,5cm x 2,13m	1 pc

Code	Dimension	Packaging
SOLL 117	83cm x 83cm x 78cm	1 pc

SPRAY STANDS, SPRAY BOOTH



SOLL WHEEL RIM HOLDER

Metal wheel rim holder suitable for stands SOLL 117, SOLL 110, SOLL 111.



SOLL FLOOR FILTER

Floor filter with elastic fibre structure for spray booths and exhaust extractors such as filtration walls. Main characteristics: up to 97% spray-dust separation; temperature resistant up to 140° C, silicone-free, acetone resistant; non-flammable in accordance to DIN 4102; basis weight approx. 220-240 g/m². Features: for the protection of paint sediment on exhaust extractors, motors and fans.



Code	Dimension	Packaging
DLC-220G 0.76	25 x 0,76 m	1 pc
DLC-250G 0.76	25 x 0,76 m	1 pc
DLC-250G 1.00	25 x 1 m	1 pc
DLC-250G 1.00	25 x 1 m	1 pc

Code	Packaging	
SOLL 122	1 pc	







SOLL CEILING FILTER 600G

White ceiling filters, impregnated with a dust adherent and are specially dense on the fresh air side in order to filter harmful particles > 10 µm, which are separated to 100% by the optimal fibre combination and the adhesive equipment. The secure fibre bonding prevents any separation of fibres during the spraying process.



SOLL TSC

It's a transparent and odourless fluid of high viscous. It is designed for protecting interior walls of spray-booths against lacquer dust deposition directly on wall panels. The coating forms a tacky, dust collecting coating. It can be applied with spray gun, brush or roller. Water soluble.

Code	Dimension	Packaging
DLAA-600G	2,05 x 20 m	1 pc

Code	Contents	Packaging
TSC-5	51	1 pc

SOLL TUBE 1000W

1000W Infra red paint curing bulb / lamp only.



Code	Dimension	Power	Packaging
350MM tube	350 mm	1 kW	1 pc
500MM tube	525 mm	1 kW	1 pc

SOLL GP-101H

Short - wave lamp for small area care baking.



Code	Dimension	Power	Packaging
SGP-101H	350 mm	1 kW	1 pc

DRAYING EQUIPMENT





SOLL GP-101

Short - wave lamp for small area care baking.



SOLL GP-333

Infrared paint dryer with stand and manual or automatic control.

Code	Dimension	Power	Packaging	
SGP-101	350 mm	1 kW	1 pc	

Code	Dimension	Power	Control System	Packaging
SGP-333	500 mm	3 kW	manual	1 pc
SGP-825M	500 mm	3 kW	automatic	1 pc



UNIVERSAL

SPRAY

White gloss Balti blizgūs daži

Sprühlack Weiß

glänzend



SOLL UNIVERSAL SPRAY

Fast drying lacquer with good coverage and excellent adhesion to treat surfaces, treated and untreated, of wood, metal, glass and various types of plastic. It is used for repairing cars with minor and medium paint damage.







SOLL TEXTURE LACQUER FOR PLASTIC

Texture paint to restore the structure of repaired surfaces of plastic. Used for the repair of bumpers, mirrors, protecting bars and dashboard.

Code	Description	Contents	Packaging
S700009	white high gloss	500 ml	6 pcs
S700001	black matt	500 ml	6 pcs
S700002	black high gloss	500 ml	6 pcs

Code	Color	Contents	Packaging
S700010	black	400 ml	6 pcs

SOL PAINTS PAINTS



SOLL KONTROL SPRAY

Kontrol spray based on nitrocellulose in combination with special alkyd resins. Black guide coat used to make irregularities visible once the putty and filler has been applied and prepared for the following sanding. It makes irregularities on the surface clearly visible. Sanding over the area intensifies the effect.





SOLL HEAT RESISTANT PAINT

Heat-resistant spray (+600 °C) for application on parts exposed to high temperatures (engines, exhausts, motorbikes) without primer and in the household (e.g. exhaust pipe - garden grill, boilers, and breeze ovens).

Code	Color	Contents	Packaging
S700030	black	400 ml	6 pcs

Code	Color	Contents	Packaging
S700012	black	400 ml	6 pcs
S700013	silver	400 ml	6 pcs

PAINTS



SOLL WHEEL SPRAY

Fast drying acryllic lacquer with lasting gloss to embellish and repair steel and light metal rims and hubcaps.



SOLL BRAKE CALIPER PAINT

Lacquer to highlight brake pads. Resistant to petrol, chemicals and weather influences. Heat resistant to 150° C.

Code	Color	Contents	Packaging	Code	Color	Contents	Packaging
S700003	silver	500 ml	6 pcs	S700026	red	400 ml	6 pcs

SOL PAINTS PAINTS

SOLL ZINC-ALU SPRAY



It is an excellent corrosion protection for all metal surfaces such as car body, door, fence or other metal structure. It is intended for the treatment of galvanized and raw steel. Suitable for spot welding.



SOLL CHROME EFFECT SPRAY

Extremely shiny, silver-colored, fast-drying decorative spray chrome acrylic paints are intended for wood, metal, aluminum, glass, stone, various types of plastic and other surfaces. Chrome paint is intended for interior work. Chrome paint is not resistant to rubbing and weathering. Chrome paint can not be covered with colorless varnish.

Code	Contents	Packaging
S700031	400 ml	6 pcs

Code	Contents	Packaging
S700032	400 ml	6 pcs



PAINTS



Pre-fill spray contains propellants, solvents and specific additives for the filling with 100 g. solvent-based basecoat.





SOLL CLEAN SYSTEM PREFILLED SPRAY

Supplied with a Fill-One cap. Pre-fill spray contains propellants, solvents and specific additives for the filling with 100 g. solvent-based basecoat.

Code	Contents	Packaging	
S700400	400 ml	6 pcs	

Code	Contents	Packaging
S700401	400 ml	6 pcs

SOL PRIMER PRIMER



SOLL HB FAST FILLER

Versatile all-purpose high build primer for various substrates, including putty, old paint (excluding thermoplastic coatings), steel, galvanized steel, aluminum, and various plastics. Offers high filling capacity, stability on vertical substrates, and fast drying. Contains anti-corrosion pigments for added protection. Ideal for spot repair and part refinishing.



SOLL ETCH FILLER

One-component self-etching filler with active corrosion protection. It provides strong filling power due to high performance spray jet and fast, efficient application. Excellent adhesion on iron, steel, zinc, and aluminum (with proper pretreatment), as well as recoatable plastics in the automotive industry (spray to test the recoatability ability).

Code	Color	Contents	Packaging	Code	Color	Contents	Packaging
S700027	grey	400 ml	6 pcs	S700028	light grey	500 ml	6 pcs

PRIMER

SOLL EPOXY PRIMER

It's an all-purpose Primer with excellent adhesion and corrosion protection on metallic substrates, various types of plastics. Can be dry grinded after 45 minutes with P400 - 500. Can be top coated with any solvent-based or waterborne basecoats as well as with 1K and 2K topcoats. Can be used "wet-on-wet".





SOLL UNIVERSAL PRIMER

Creates a smooth surface, an ideal base for a subsequent covering coat, fills small irregularities. It can be applied on any surface and easy to sand down.

Code	Color	Contents	Packaging
S700029	grey	400 ml	6 pcs
S700029W	white	400 ml	6 pcs
S700029B	black	400 ml	6 pcs

Code	Color	Contents	Packaging
S700005	grey	500 ml	6 pcs
S700006	white	500 ml	6 pcs
S700007	black	500 ml	6 pcs





PRIMER, PUTTY



Primer for plastic parts, such as wing mirrors, bumpers, spoilers etc. Plastic adhesion primer allows conventional plastic parts on the outside vehicles to be painted and it results in an excellent adhesion for subsequent coatings.



SOLL SPRAY PUTTY

Fast drying spray putty with excellent filling properties and coverage to fill small irregularities in surfaces, treated and untreated, of wood, metal and aluminium.

Code	Color	Contents	Packaging	Code	Color	Contents	Packaging
S700011	transparent	400 ml	6 pcs	S700023	grey	400 ml	6 pcs



VARNISHES



SOLL CLEARCOAT

It's a transparent special combination lacquer of high quality. Suitable for surfaces of metal, wood, ceramics, stone, clay, glass, paper and plastics. Can be used at home, garden, workshop, hobby indoors and out.





SOLL BACKLIGHT

Transparent lacquer to highlight backlights. Has a lasting gloss and is scratch free and shock proof.

Code	Description	Contents	Packaging
S700004	gloss	500 ml	6 pcs
S700021	matt	400 ml	6 pcs

Code	Color	Contents	Packaging
S700015	black	150 ml	20 pcs
S700016	red	150 ml	20 pcs











SOLL HAND CLEANER PREMIUM

Intensive hand cleaner with grains is suitable for paints that are extremely difficult to remove, resins, glues, bitumen, silicone and other dirt. Due to the fast and efficient cleaning effect of the paint, it is especially suitable for painters. Made from the highest quality raw materials, it does not contain substances that can irritate and damage the skin.

Code	Description	Packaging
S-HCP 250	250 ml	12 pc
S-HCP 3000	3	6 pcs
500223	Dispencer for 3 ltr hand cleaner tin	50 pcs

PROTECTION



SOLL NYLON OVERALL

It is a blue, extremely light, painter overall made of a continuous nylon type breathable fabric. The overall has a hood, is tear resistant, lint-free, antistatic, silicone free, impermeable to paint and fire resistant, for use in paint shops.

Code	Size	Packaging
SNO M	М	1 pc
SNO L	L	1 pc
SNO XL	XL	1 pc
SNO XXL	XXL	1 pc

SOLL NITRILE HEAVY DUTY GLOVES, BLACK

High quality nitrile gloves, powder free. Resistant to weak acids, chemicals. Extremely elastic and comfortable to wear. Nitrile gloves do not cause an allergic reaction.



Code	Size	Packaging
SNG-L	L	10 pcs
SNG-XL	XL	10 pcs



POLISHING PASTE

One step Solding - polishing path Soliding - polishing path Soliding

SOLL ONE STEP

A new concept-based, high efficiency, abrasive grinding polishing paste "ONE STEP" used for polishing each new and old coating. The paste "ONE STEP" is suitable for all types of polishing discs.





SOLL UNIVERSAL

This fast acting liquid abrasive removes sanding scratches from refinished or original paintwork. Applied using a machine polisher. UNIVERSAL compound is easy to use and guarantees a high gloss finish.



Code	Contents	Packaging
SPP-417	1 kg	12 pcs
SPP-417-250	250 g	24 pcs

Code	Contents	Packaging
SPP-250	250 g	24 pcs
SPP-1	1 kg	12 pcs

POLISHING PASTE

SOLL POLISHING COMPOUND

Three steps polishing compound.









Code	Description	Contents	Packaging
SPP-74-250	Fast 74	250 g	24 pcs
SPP-74	Fast 74	1 kg	12 pcs
SPP-75	Medium 75	1 kg	12 pcs
SPP-76	Finish 76	1 kg	12 pcs

SOLL MATT



SOLL matting compound is a combination of scuffing and cleaning gel for preparing original or refinish paints prior to fading out base coats and/or applying clear coats, single colour top coats or blending out clear coats and single colour top coats.

Code	Contents	Packaging
SPP-18	400 g	20 pcs

Packaging

1 pc

TOOLS



SM6-15

15 mm

1800-4800 rpm

1000 W

3,5 kg

TOOLS

SOLL SPARE PARTS FOR POLISHERS

SSW - SOLL Switch for SOLL SM6-15 polishing mashine. SBR - Carbon brushes SBR (2 pcs.) for SOLL SM6-15 polishing machine. SCB05 - Carbon brushes (2 pcs.) for SOLL SPR05 polishing mashine.



Code	Description	Packaging
SSW	Switch	1 pc
SBR	Brushes	2 pcs
SCB05	Brushes	2 pcs

SOLL ELECTRIC ROTARY POLISHER

Characterized by a steady gradual acceleration to maximum speed without a sudden jerk. Constant speed ensures efficiency even under heavy loads. Speed selection available for all polishing jobs. Also, good cooling ensures that the tool does not overheat during the long process. The D-shaped handle ensures ideal control of the device. Easily replaceable carbon brushes.

Code	Disc	Speed	Power	Packaging
SRP05	180 mm	600-3200 rpm	1500 W	1 pc

TOOLS TOOLS

SOLL POLISHING PAD

Foam polishing pad with velcro backing system.



Code	Description	Dimension	Packaging
SPD-VH	hard	Ø150 x 50 mm	18 pcs
SPD-VM	medium	Ø150 x 50 mm	18 pcs
SPD-VS	soft	Ø150 x 50 mm	18 pcs
SPD-VG	green	Ø150 x 25 mm	36 pcs

SOLL POLISHING PAD

Foam polishing pad with M14 tread plastic backing system.



Code	Description	Dimension	Packaging
SPD-M14H	hard	Ø150 x 50 mm	12 pcs
SPD-M14M	medium	Ø150 x 50 mm	12 pcs
SPD-M14S	soft	Ø150 x 50 mm	12 pcs
SPD-M14G	green	Ø150 x 50 mm	12 pcs

TOOLS

SOLL POLISHING PAD

Foam polishing pad with Velcro backing system. Dimension: Ø 150 mm x 25 mm



Code	Color	Hardness	Description	Packaging
DA-RV 2	light green	medium	open cells	36 pcs
DA-RV 5	white	hard	open cells	36 pcs
DA-RV 6	green	medium	closed cells	36 pcs
DA-RV 10	blue	medium - hard	open cells	36 pcs
DA-RV 14	yellow	soft	open cells	36 pcs

SOLL WHITE POLISHING PAD

Hard foam polishing pad.





Code	Fastening	Dimension	Packaging
SPD-VH-80	Velcro	Ø 80 mm x 25 mm	50 pcs
SPD-M14H-80	M14	Ø 80 mm x 25 mm	50 pcs

SOL TOOLS TOOLS



SOLL WAFFLE FOAM POLISHING PAD

Removes light swirl marks and light compounding haze. Use this pad with a finishing polish to create a high-gloss, swirl-free shine.

Code	Color	Dimension	Packaging
SPD-180WW	white	Ø 180 mm	20 pcs
SPD-180WB	black	Ø 180 mm	20 pcs
SPD-180WO	orange	Ø 180 mm	20 pcs

Code	Color	Dimension	Packaging
SPD-210WW	white	Ø 210 mm	20 pcs
SPD-210WB	black	Ø 210 mm	20 pcs
SPD-210WO	orange	Ø 210 mm	20 pcs

TOOLS



SOLL POLISOFT POLISHING WIPES

Soft fabric polishing wipes for coarse particles and gentle cleaning of the surface.

Code	Description	Dimension	Packaging
S400301	in sheets	32 cm x 36 cm	50 pcs



